















The length of rope is measured in fathoms (1 fathom = 6 feet).
The size of a rope is measured by its circumference in inches.



A CRUISER'S MAINMAST



TRUCK

W/T YARD

TOPMAST

CAP

LOWER MASTHEAD

SIGNAL YARD

LOWER MAST

BACK STAYS

MAINMAST SHROUDS
MAINTOPMAST SHROUDS

INSULATORS


LIFTS

GAFF

FOOT-ROPE

BOTTLE-SCREW AND SLIP,
FOR SETTING UP
LOWER ENDS
OF
STANDING RIGGING

EYE




PARTS OF A BLOCK



LUFF



TAIL
JIGGER



HANDY
BILLY

FIG. 50


Orders for working a Derrick

Single Whip

To hoist the weight :	“ Hoist away.”	“ Up purchase.”
To stop hoisting :	“ High enough.”	“ High enough.”
To lower the weight :	“ Lower away.”	“ Lower purchase.”
To stop lowering :	“ Avast lowering.”	“ Stop purchase.”
To work guys :	“ Tend your guys.”	
	“ Haul away [or check] your fore [or after] guy.”	

Topping Lift

To raise the head of the derrick :	“ Up topping lift.”
To lower the head of the derrick :	“ Lower topping lift.”
To stop raising :	“ High enough topping lift.”
To stop lowering :	“ Avast lowering.”
	(<i>Single Whip, Light, with no load</i>)
To raise the hook quickly :	“ Up whip.”



HEAD

TOPPING-LIFT

STANDING TOPPING LIFT

FORE GUY

WHIP

AFTER GUY

'BACKING-UP'

MOTOR BOLLARD

HEEL


LEADING BLOCK

SHIP'S PORT SIDE

Single block




Fall



Fall

Leading block

Eye bolt



Fall

Leading Parts

Single block

Leading Parts










www.westernaspect.com



A CRUISER'S MAINMAST



A CRUISER'S MAINMAST








Fig. 1




Fig. 2





Fig. 3 Lashing





008198
8618002



